

便携式移动演播室

# HD 12通道便携式移动演播室

## HS-3200

视频系统	Full HD
视频格式	1080p 25/29.97/30/50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz
输入设置[XPT]	All 12, repeatable
视频输入	8x SDI, 4x HDMI
计算机输入	4 via HDMI
下变换转换器	1x SDI
视频输出	5x SDI, 1x HDMI assignable: Multiview, PGM, PVW, PGM+DSK, Clean PGM, Clean PVW, Input 1-12, STILL 1, STILL 2, Flex source 3x HDMI PGM only
音频输入	4x Balanced XLR
音频输出	2x Balanced XLR
音频嵌入	Input 2 channels, Output 4 channels
音频延迟	Up to 16 frames
音频同步切换	Yes
USK	4
DSK	2, support Lumakey & Linear key (Key / Fill)
画中画	8 (4x Keyer, 4x Flex Source)
LOGO	2
字幕机	Yes,
调音台	----
监看屏幕	17.3英寸高清薄膜晶体管液晶显示器[1920x1080像素
通话系统	----

### 直播串流规格

串流视频编码	H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 10Mbps
串流音频编码	AAC-LC Configurable bit rate range from 32Kbps to 384Kbps Sample rate: 48KHz, 16bit
串流协议	TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP/RTMPS (Publish) HLS SRT

串流控制	Web browser UI for configuration and control Socket commands
录制设定控制	Web UI for system configuration and control
录制文件系统	FAT, exFAT, NTFS
录制文件格式	MP4

## 其他规格

特别功能	4 Chroma-Key Virtual Studio 9 stinger transition and 4 user preset Built in TC-200 CG interface Streaming encoder and recorder 12x9 matrix seamless switch
尺寸	455 x 355 x 134 mm
重量	17.8 Lbs (8.1 kg), Reinforce Plastic Case
电源	DC 12V, 11A
操作温度	0~40 °C
包装明细	1 x HS-3200 主机 1 x 12V电源适配器 1 x 电源线 1 x 64G SD卡