

音视频追踪切换设备

智能声像追踪视听系统**VTRX-100**

控制方式	可进行系统配置与管理的网页页面
控制协议	DVIP
网络寻址方式	网络接口□1x RJ-45 接口 (10/100/1000M 以太网) 寻址方式□DHCP或固定 IP
POE规格	IEEE 802.3at
固件更新	自动固件升级
电源规格	输入交流100~240V可调节电源适配器 输出直流12V/1A
视频输出接口	2 组HDMI 2.0接口
视频输出格式	3840x2160p: 30/29.97/25/24/23.98 (仅H.265模式支持) 1080p: 30/29.97/25/24/23.98 1080i: 60/59.94/50, 720p: 60/59.94/50 576i 50 (PAL) 480i 60 (NTSC)
支持切换台种类	iCast 10NDI, iCast 10NDI MKII, KMU-100 SE-2600, SE-4000, SE-3200 SE-650, SE-1200MU, SE-2600MU
支持麦克风种类	Ai Speech MC-10A Audio-Technica ATND1061 Audio-Technica ATUC-IR Audio-Technica ATUC-50 Bosch DICENTIS Wireless Bosch CCS-1000D Relacart ACM-335 Relacart ACM-582 Sennheiser TCCM Sennheiser TCC2 Shure MXW Microflex Shure MXA-910 Shure MXA-920 USB Audio Mixers / Interfaces: Allen and Heath CQ12T Allen and Heath CQ18T Zoom LiveTrak L6 Zoom LiveTrak L6 Max Zoom LiveTrak L8 Zoom LiveTrak L12 RodeCaster Pro II SoundCraft UI24R M-Audio Duo M-Audio Air 192 14 Tascam US-16X08 Tascam Mixcast 4 Behringer UMC404HD

